



## 'TIS THE SEASON FOR BABY LOCK!

### Christmas Quilt



Each block in this quilt has only three seams and takes 10 minutes. With the use of the Baby Lock Jazz sewing and quilting machine you are on your way to create a quilt that you could snuggle up with or pretty enough to hang on your wall.

#### **Skill Level: Easy**

Created by: Diane Kron, Software and Embroidery Project Manager

#### **Supplies:**

Baby Lock® Jazz sewing machine  
Christmas Layer Cake print fabric (10" cut squares)  
Backing fabric  
½ Yard of red cotton fabric for binding  
Madeira® Cotona and quilting thread  
Batting  
Temporary spray adhesive

Quilt Size: 47" x 57"

**Instructions:**

1. Separate the 10" layer cake squares by colors (lights and darks). Six of the light colors will be used for the stained glass sections (*as shown below inside each of the six green boxes*). The darks squares will be used to form the larger sections around the stained glass areas. Follow the next set of directions to complete the one block:



- Take one of the light colored squares and fold it in half. Lay it on a flat surface with the folded edge facing away from you.
- With right sides together, place one of the darker squares under the folded section and one on top (*as shown in the following illustration*).



- Sew the right edge using  $\frac{1}{4}$ " seam allowance.

- Take two more of the darker fabrics and place one under and one over the folded section as done in the prior step.
- Pin the sections together.
- Sew the second seam.



- Press the seams.
- With the three sewn pieces laying on a flat surface, bring the two top large side pieces together with right sides facing. Pin in place. Do the same for the other side. The light colored section in the center should open out to form a triangle shape inside the sandwiched area. Center the seam on the top with the seam on the bottom. Smooth out the center section so that it lies flat with the edges lining up with the edges on the darker sections (*as shown in the illustration below*). Pin in place.
- Using a  $\frac{1}{4}$  seam allowance sew the third seam on the block.





- On the front of the block, press the block carefully lining up the points with the each of the seams. Set aside.
2. Make 5 more blocks following the same directions as above.
  3. Cut six fabric squares in half to create 12 pieces that measure 10" x 5".
  4. Lay the six blocks on a flat surface. Place the 10" x 5" pieces on each of the sides. Create three rows. Sew the sections together to make the rows. Sew the rows together to form the quilt top.
  5. Make a sandwich with the backing, batting and the quilt top.
  6. Lightly spray between the layers using the temporary spray adhesive or you can pin the quilt with quilt safety pins.
  7. Starting in the middle of the quilt, roll the four edges on each of the six light colored diamond areas toward the center of the block. Pin to hold in place.
  8. Stitch through all of the layers to secure (*as shown in the following illustration*).



9. Set up the machine for quilting:
  - Lower the feed dogs.
  - Wind several bobbins using the same thread that will be used for the top thread.
  - Attach the quilting foot.
  - Thread the machine.
  - Place the bobbin in the bobbin case.
  - Select a straight stitch.
  - Make a small sandwich using the same fabrics as used in the quilt.
  - Do a test sew to see the tension and to become comfortable with the quilting of the stippling stitch.

- Adjust the tension as needed.
  - Quilt the quilt as desired.
10. Trim all four edges.
11. To make the binding follow the next set of steps:
- Cut several 2 ½" wide strips across the width of the fabric.
  - Piece the sections together to make one long strip that will fit around the outer edge of the quilt.
  - Fold the long sides with wrong sides together and iron.
  - Turn in one of the short ends at a 45° angle.
  - Place the short end 6" down from the top corner on the front of the quilt with the raw edges even and pin in place.
  - Start to sew the binding to the quilt 4" down from the beginning of the binding strip.
  - Stop sewing and cut the thread ¼" from the corner.
  - Fold the binding strip up and away from the quilt so that the binding makes a 45° angle at the corner on the quilt. Finger press at the corner. Fold the binding down over the second side of the quilt so that the raw edges are even.
  - Sew down the second side of the quilt and stop ¼" from the corner and cut the thread. Repeat these steps to finish sewing the binding to the quilt.
  - After you have turned the last corner, cut the end of the binding so that it will fit inside the starting point at the bias strips starting point. Continue to sew the binding to the quilt.
  - Fold the binding to the back of the quilt.
  - Hand sew the binding in place.

For other exciting projects like this one, visit our website at [www.babylock.com](http://www.babylock.com).

